

ARK



Profilo LED a "C" per installazione a plafone, parete, sospensione ed incasso in cartongesso di spessore 12,5 mm, ad emissione diretta.

Corpo in estruso di alluminio e rosoni in acciaio verniciato a polvere, schermo diffusore in PMMA opale.

Per installazione a plafone/parete, prevedere alimentazione remota da ordinare a parte.

Per installazione ad incasso, staffe di fissaggio in acciaio ed alimentazione remota da ordinare a parte.

Per installazione a sospensione prevedere rosoni con alimentazione integrata, oppure rosoni per alimentazione remota unitamente a kit di sospensione e cavi di alimentazione da ordinare separatamente.

Alimentazione elettronica 220-240V 50/60Hz disponibile anche dimmerabile DALI-PUSH.

"C" LED Profile for ceiling, wall, suspension and recessed mounting for 12,5mm thick plasterboard, for direct light emission.



Body made of extruded aluminium, canopy made of powder coated steel and PMMA opal diffuser.

For ceiling/wall mounting it is required remote driver to be ordered separately.

For recessed mounting, steel brackets and remote driver to be ordered separately.

For suspension mounting it is required canopy with integrated driver, or canopy for remote driver and suspension kit and power cables, to be ordered separately.

Electronic driver 220-240V 50/60Hz is also available DALI-PUSH.



ARK 962

Testate terminali include

End caps included



2700K


Ø (mm)	POWER	CODE	01 FLUX	02	20	21	22 FLUX
962	42W	109801_..	01 3095 lm	02	20	21 2631 lm	22 2786 lm

3000K

Ø (mm)	POWER	CODE	01 FLUX	02	20	21	22 FLUX
962	42W	109802_..	01 3239 lm	02	20	21 2753 lm	22 2915 lm

4000K

Ø (mm)	POWER	CODE	01 FLUX	02	20	21	22 FLUX
962	42W	109803_..	01 3497 lm	02	20	21 2973 lm	22 3147 lm



ARK 1440

Testate terminali include

End caps included



2700K

Ø (mm)	POWER	CODE	01 FLUX	02	20	21	22 FLUX
1440	62W	109804_..	01 4643 lm	02	20	21 3947 lm	22 4179 lm

3000K

Ø (mm)	POWER	CODE	01 FLUX	02	20	21	22 FLUX
1440	62W	109805_..	01 4159 lm	02	20	21 4130 lm	22 4373 lm

4000K

Ø (mm)	POWER	CODE	01 FLUX	02	20	21	22 FLUX
1440	62W	109806_..	01 5246 lm	02	20	21 4459 lm	22 4721 lm