


HALOS MINI APPLIQUE



Profilo LED circolare per installazione a parete a luce interna.
Corpo in estruso di alluminio verniciato a polvere e schermo in PMMA opale.
Staffe per il montaggio a parete integrate, alimentazione remota da ordinare a parte.

Circular LED profile for wall surface mounting with internal light emission.
Body in powder-coated extruded aluminium and PMMA opal screen.
Integrated wall mounting brackets, remote power supply to be ordered separately.




HALOS MINI APPLIQUE 482

2700K						
Ø (mm)	POWER	CODE	<input type="checkbox"/> FLUX	<input checked="" type="checkbox"/> FLUX	<input checked="" type="checkbox"/> FLUX	<input checked="" type="checkbox"/> FLUX
482	24W	107348...	01 1331 lm	02 1131 lm	20 1131 lm	21 1131 lm 22 1197 lm
3000K						
Ø (mm)	POWER	CODE	<input type="checkbox"/> FLUX	<input checked="" type="checkbox"/> FLUX	<input checked="" type="checkbox"/> FLUX	<input checked="" type="checkbox"/> FLUX
482	24W	107349...	01 1435 lm	02 1219 lm	20 1219 lm	21 1219 lm 22 1291 lm
4000K						
Ø (mm)	POWER	CODE	<input type="checkbox"/> FLUX	<input checked="" type="checkbox"/> FLUX	<input checked="" type="checkbox"/> FLUX	<input checked="" type="checkbox"/> FLUX
482	24W	107350...	01 1472 lm	02 1251 lm	20 1251 lm	21 1251 lm 22 1324 lm

HALOS MINI APPLIQUE

ACCESSORI ACCESSORIES



ALIMENTATORE ELETTRONICO
220-240V 50/60Hz

CODE	VERSION	D (mm)	A (mm)	H (mm)	L (mm)
* 107324.99	482 mm	54	44	30	147

ELECTRONIC DRIVER
220-240V 50/60Hz

DALI-PUSH

CODE	VERSION	D (mm)	A (mm)	H (mm)	L (mm)
107325.99	482 mm	86	80	30	124

