

EASY UP SIDE

Electrically elevating structure with return
Struttura elevabile elettricamente con allungo



DATA SHEET

- **Height Range:** 27.2"-46.5"/690-1180mm
- **Supporting Beam Width Range:** 43.3"-74.8"/1100-1900mm
- **Auxiliary Beam Width Range:** 49.6"-73.2"/1260-1860mm
- **RECOMMENDED TABLETOP DIMENSIONS:**
 - Main 47.2"-78.7"/1200-2000mm (Lenght)
 - Vice 51.2"-70.9"/1300-1800mm (Lenght)
 - 23.6"-31.5"/600-800mm (Depth)
- **Load Capacity:** 330lbs/150kg
- **Speed:** 32mm/s
- **Noise Level:** <50 dB
- **Low Standby Power:** <0.5W
- Holeless Design Column
- Optional Control Panel
- **Surface:** Spray Color White or Anthracite
- Built-in Sensor Anti-pinch Function, Anti-collision Function (Adjust the corresponding function according to the gear)
- **Related Product Component Certification:** CB, CE-EMC, CE-LVD, RoHS, FCC, UL, CUL, RCM etc.

DEFAULT CONTROL PANEL



Seven-Button Remote
Digital Height Display
Three Programmable Positions
Time Reminder
(HS11A-1)

DIMENSIONAL DIAGRAMS

